

APPLICATION FOR LETTERS PATENT

FOR

REMOTE CONTROL ELECTRONIC DISPLAY SYSTEM

INVENTOR: DAVID GOTHARD

Prepared by:

Robert J. Schaap, Esq.
21241 Ventura Boulevard
Suite 188
Woodland Hills, California 91364

(818) 346-6555

SPECIFICATION

BE IT KNOWN THAT I, DAVID GOTHARD, a citizen of the United States and resident of the City of Henderson, State of Nevada, have
5 invented a certain new and useful REMOTE CONTROL ELECTRONIC DISPLAY SYSTEM of which the following is a specification containing the best mode of the invention known to me at the time of filing an application for letters patent therefore.

BACKGROUND OF THE INVENTION

1. Field Of The Invention.

5 This invention relates in general to certain new and useful improvements in display signs, and more particularly, to remotely controlled electronically operable display signs in which a display on a sign may be changed at will from a remote source, and methods of displaying information in such manner that the sign is used as an instrument to enhance the image of a product or service.

2. Brief Description Of Related Art.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945
9950
9955
9960
9965
9970
9975
9980
9985
9990
9995
10000
10005
10010
10015
10020
10025
10030
10035
10040
10045
10050
10055
10060
10065
10070
10075
10080
10085
10090
10095
10100
10105
10110
10115
10120
10125
10130
10135
10140
10145
10150
10155
10160
10165
10170
10175
10180
10185
10190
10195
10200
10205
10210
10215
10220
10225
10230
10235
1

located along portions of the periphery of the frame. In some cases, when using a somewhat transparent or translucent sheet, back lighting may also be employed.

5 The cost of preparing display signs made with paper and paper-board substrates can be quite substantial. Initially, the art work must be prepared often times by hand, although certain computer aids for purposes of preparing the drawing may be available. Nevertheless, preparation of the drawing is labor intensive. Thereafter, multi-color printing is usually required in order to
10 complete the preparation of the paper or paper-board sign or display. These various steps, as indicated, are labor intensive and therefore materially add to the overall costs of preparing a sign or display, particularly when made of a paper or paper-board material.

15 In addition to the foregoing, there are also costs involved in the shipping or transport of these signs. Generally, they cannot be folded or bent or they would otherwise be unsuitable for use. As a result, special precautions and shipping containers must be provided for transport of the paper or paper-board substrate signs
20 or displays.

There have also been display signs which use a frame and a source of light along with a glass or plexiglass sheet having an image or other information literally formed on the sheet, as for example, by means of glass etching, masking, or the like. However,
25 with this type of display, when it is necessary or desirable to change the display in the sign, it is necessary to prepare a new

piece of glass or plexiglass or otherwise a masking on a rear surface thereof having other information presented thereon.

Here again, the cost of preparing an etched glass sheet can be quite substantial. The same also holds true of the outer transparent sheets with masks on the rear surface thereof to create a design or display with that sheet. Again, because of the frailty of these sheets; substantial precautions must be taken for the transport or shipment of these sheets.

There is presently no display sign capable of having information changed thereon as quickly as information can be changed on the screen of a computer monitor. Moreover, and independently thereof, there is presently no effective display sign which can be changed from a remote location.

OBJECTS OF THE INVENTION

It is, therefore, one of the primary objects of the present invention to provide an electronic display sign which uses a flat panel display image and which can readily be changed in accordance with electronic signals applied thereto.

It is another object of the present invention to provide an electronic display sign of the type stated which can be altered rapidly through the use of a computer or otherwise through an image scanner.

It is a further object of the present invention to provide an electronic display sign of the type stated which can be controlled from a remote source and the display on the sign can be changed at will from that remote source.

It is an additional object of the present invention to provide a display sign of the type stated which completely eliminates the need for interchangeable substrates bearing the information to be displayed.

It is also an object of the present invention to provide an electronic display sign and a method of altering a display on a sign electronically and without using interchangeable substrates bearing information to be displayed.

It is another salient object of the present invention to provide a method of displaying information by generating that information from a remote source and transmitting that information to a display sign.

It is still another object of the present invention to provide a unique circuit enabling operation of a display sign from a remote source.

5 It is still a further object of the present invention to provide a method of displaying information on the screen of the display sign, potentially along with other external action, such as the addition of sound or the like, to enhance a product or a service on the display sign.

10 It is yet another object of the present of the invention to provide a display sign of the type stated which can be used to provide value plus advertising and which also enables the use of animation with respect to any message displayed thereon.

15 With the above and other objects in view, my invention resides in the novel features of form, construction, arrangement and combination of parts presently described and pointed out in the claims.

BRIEF SUMMARY OF THE INVENTION

The present invention relates in general terms to a display system including a display sign which is electronically accessible from a remote source and which enables the almost automatic change of a display pursuant to control of an operator at the remote source. In a broad sense, the display system of the present invention comprises a display sign having a display panel thereon as well as display generating means at the remote source for generating a display to be displayed on that display panel. The display is actually generated in the form of an electrical signal and the system comprises a transmitting means for transmitting the electrical signal representing the display to the display panel of that display sign.

The present invention also provides a method of generating a display on a display sign from a remote source. The method involves the steps of generating the display and then transmitting that display to the display sign in the form of electrical signals representing the display. The display sign is provided with electronics using the received electrical signal to recreate the generated display and present same on the display panel.

In one embodiment of the invention, the means for transmitting the display is an electrical conductor connected between the display sign and the display generating means at the remote source. In another embodiment of the invention, the means for transmitting the display is a wireless transmission means, such as by means of radio frequency transmission, satellite transmission, or the like.

In a more preferred embodiment of the invention, the means for generating the display comprises an image generating means which enables the generation of initial image forming part of the display and a temporary storage for temporarily storing that image. Editing means are also provided for adding material to or otherwise modifying the image. Thereafter, a permanent storage is provided to enable storage of the generated display in electrical format, at least until such time as transmission thereof to the display sign.

In still a more preferred embodiment, the apparatus comprises a scanning means for scanning a particular image and converting the image into electrical signals representative thereof. The image is then stored in the temporary storage. A keyboard input may be connected to that temporary storage for introducing information through a keyboard input. In addition, means is provided for adding other copy material. Thereafter, all of the material added can be edited by an operator to form a display. The display is then stored in a permanent storage.

It is also possible to generate a display, or to otherwise add information to a display, or otherwise alter a display by means of information introduced over the world wide web. Thus, various inputs can be made from a variety of sources and all of which can be processed and added to or otherwise used to modify a proposed image, as may be desired.

At a predetermined time, the stored display can then be transmitted to a storage in the sign. Moreover, a plurality of different displays can be stored at the remote source and these

displays can be sequentially transmitted to the display sign. In this way, an operator can manually or automatically control the generation of a plurality of desired displays in a predetermined time sequence.

5 The present invention not only allows for the display to be generated at the sign from a remote source, but it also allows for a plurality of displays to be presented in a desired format and in a desired predetermined time arrangement, as aforesaid. As a result, there is no need to use hard copy displays, such as pre-
10 printed paper displays. Furthermore, minor changes can be electronically made in a display as, for example, minor price changes can be made without the necessity of re-printing.

15 The display sign is also of a unique construction in that it comprises means for controlling certain atmospheric conditions and, particularly, temperature in the display sign. Furthermore, an interference filter is formed on the surface of the display panel to preclude excess heat generation within the display sign. The display panel is preferably a plasma display, as hereinafter described in more detail.

20 The display sign preferably includes an outer housing which may be provided with a removable front face or so-called "cover". The front face is provided with an enlarged opening in order to enable a display panel to appear through that opening. A transparent protective sheet may be disposed over the display
25 panel.

The housing is in the form of a rectangularly shaped box, although it may adopt other shapes. The major components which enable the display including the display panel are preferably mounted on a separate chassis to enable easy and convenient assembly of the display sign. The separate chassis is secured through the display box to a mounting station, such as a display stand. In this way, only one having authorized access to the interior of the display housing can disconnect the chassis and the mounting station.

The chassis in the preferred embodiment includes a power supply for operating the plasma display panel. In addition, the chassis may also comprise a second power supply for operation of a processor or computer within the housing. The computer is designed for connection to the temporary storage at the remote source and will receive generated displays in electrical signal format. The computer is programed to recreate those displays at the sign and generate the same through the plasma display panel. For this purpose, the computer is also mounted on the chassis.

The housing is preferably provided with a plurality of openings extending primarily throughout the side wall thereof. Moreover, venting fans may also be provided for venting heated air in the housing to the exterior.

The foregoing objects and the advantages of this invention have been met and fulfilled by this system and method which has been briefly described in the general description. However, the invention will now be described in more detail in the following

detailed description and in the accompanying drawings. Nevertheless, it is to be understood that these drawings and the following detailed description are only set forth for purposes of illustrating the general principles of the invention. Therefore,
5 it should be understood that the accompanying drawings and the detailed description are not to be taken in a limiting sense.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

BRIEF DESCRIPTION OF THE DRAWINGS

Having thus described the invention in general terms, reference will now be made to the accompanying drawings in which:

Figure 1 is a schematic component view showing those elements necessary for generating a display either through hard wired conveyance or otherwise wireless conveyance of information;

Figure 2 is a schematic circuit diagram showing major components necessary involved in the generation of an electronic display from a remote source;

Figure 3 is a schematic flow diagram showing those steps involved in generating a display from a remote source;

Figure 4 is a perspective view of one form of display sign constructed in accordance with and embodying the present invention;

Figure 5 is a side elevational view of the display sign of Figure 4;

Figure 6 is a perspective view of a lid or cover which extends over the display sign;

Figure 7 is a fragmentary vertical sectional view taken along line 7-7 of Figure 6;

Figure 8 is a vertical sectional view, similar to Figure 7, and showing a slightly modified form of cover used with the display sign of the present invention;

Figure 9 is an exploded perspective view showing some of the major components in the display sign of the present invention;

Sub
B2

Figure 10 is an exploded fragmentary perspective view, partially broken away, and somewhat similar to Figure 9, and showing the various components in their assembled position;

Figure 11 is a fragmentary sectional view showing one form of panel construction used in the present invention;

Figure 12 is a perspective view showing one type of mounting for a display sign constructed in accordance with and embodying the present invention; and

Figure 13 is a fragmentary perspective view showing a modified form of display sign constructed in accordance with and embodying the present invention.

Fig 14

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

Referring now in more detail and by reference characters to the drawings, Figure 1 illustrates the major components forming part of a display system D in accordance with the present invention. This display system primarily shows the generation of a display from electrical signals representative of that display at a remote location and transmission to a display sign for recreation on that display sign.

In accordance with the schematic illustration of Figure 1, the display system D comprises a display sign 20. Incorporated within the display sign 20 or otherwise being connected to the display sign is a sign controller 22. This controller may adopt the form of a microprocessor or computer in the sign and preferably includes a storage, as hereinafter described in more detail.

The display system D of the invention further comprises a display generating means 24 at a remote source and which is usually comprised of a computer 26 which may adopt the form of a processor and storage, as well as a scanner 28. In the embodiment of the invention as shown, the scanner receives ad copy 30 and generates a display in electrical format which can then be transmitted from the computer 26 to the display sign 20.

One of more inputs from the world wide web can also be connected to the computer 26, as shown in Figure 1, for aiding in or otherwise being used to generate the copy which is to be displayed on the plasma display screen 20. The computer 26, in the embodiment as illustrated, may be located at a remote site with

respect to the display sign 20. However, it should also be understood that the display sign 20 also includes its own internal computer so that the entire display is essentially self-contained and can be operated without communication with a remote source.

5 However, the remote source is needed in order to change any display which may otherwise be stored in the memory of the computer at the display screen, or to otherwise modify the manner in which the display is made.

Figure 1 also illustrates both a hard wire conductor means for transmitting the generated display, as well as a wireless means for transmitting the generated display. For the purposes of hard wire conductor transmission, the computer 26 is provided with a modem 32 and the controller 22, and the display sign 20 is similarly provided with a corresponding modem 34. As indicated previously,

15 wireless transmission is also available and could adopt the form of microwave signal transmission, radio frequency transmission, including satellite transmission, or the like. In this respect, the signal which is generated is still an electrical signal in either radio frequency format or other wireless transmission format

20 for wireless transmission. For purposes of wireless transmission, a satellite 36, as shown, may be employed, such that the wireless transmission will follow the path 38 shown in the dotted lines of Figure 1.

Figure 2 illustrates those major components forming part of the display system of the present invention. In this case, the display system comprises the scanner 28 which is usually employed

for purposes of generating the initial image. Typically, a pre-prepared image of the element to be displayed is used and scanned from the scanner 28 into a temporary storage 40. The image to be scanned by the scanner 28 may be a pre-drawn image or otherwise, it can be an image adopted from an existing source. The scanner 28 will effectively digitize the image and thereby store that digitized image into the temporary storage 40.

A keyboard input 42 is also connected to the temporary storage 40 for introducing information, such as typewritten information, into that storage. The temporary storage 40 also receives an input from a world wide web 43 and which is schematically illustrated in Figure 2. In effect, the world wide web would actually constitute one or more inputs from computer transmission lines.

The temporary storage 40 operates in conjunction with a processor 44 and a manually operable editor 46. The editor 46 is primarily designed to manipulate the images introduced into the processor 44 and the information from the keyboard input 42 into a desired format. Thus, a user of the system can manually superpose one image over another or otherwise modify two images by blending them together, etc. The editor 46 merely contains controls to enable the processor 44 to perform those functions. In this sense, the editor could also be another keyboard input much in the same manner as a computer keyboard input.

The information from the temporary storage 40 is then introduced into a permanent storage 48 where it can be retained, either indefinitely, or at least until such time as it is

transmitted to a display sign, as hereinafter described in more detail.

The display system of the invention may also comprise a transmitting means 50 in the form of a transmitter, which is schematically illustrated in Figure 2. The transmitter means 50 may adopt any conventional form of a transmission means as, for example, the modems 32 and 34, or otherwise for wireless transmission, a radio frequency transmitter, etc.

The aforesaid components constitute those major components which will form part of the display system and the remote site. Thereafter, the images which form the displays along with the other incorporated information therein can be transmitted to a display storage 60 located at and forming part of a display sign 20. The display sign 20, through its own processor, as hereinafter described, enables the generation of a display on a display panel 64 forming part of the display sign 20. The display panel 64 is also hereinafter described in more detail.

The display sign 20 may form part of or otherwise may be mounted on a stand 66, as best shown in Figure 12. The stand 66 conventionally includes a base 68 as well as an upstanding leg 70, the latter of which would engage and support the display sign 20. However, it should also be understood that the display sign 20 could be provided with a mounting means, as hereinafter described, for mounting to a wall or like structure.

Figure 3 illustrates some of the major steps associated with the method for generating a display from a remote source. In this

case, it can be seen that an image, such as an advertising image, is scanned and digitized for introduction into a temporary storage, such as the temporary storage 40. Again, keyboard input information is also provided, as well as other copy information, as shown in Figure 3. This other copy information is typically introduced through the scanner 28.

After the display has been formed, it is stored in the permanent storage 48 and then introduced into the display storage 60. Figure 3 also illustrates a rotational sequence program which can be used at the remote site or at the display sign. Thus, various displays can be generated in sequence at the display sign and at pre-determined time intervals.

The display sign 20 is more fully illustrated in Figures 5-11 of the drawings. The display sign 20 generally comprises an outer housing 72, such as a rectangularly shaped housing. The housing is preferably formed of a metal and even more preferably a light weight metal, such as aluminum, although it could be formed of steel or other structural materials. In this respect, the housing could also be formed of plastics and even reinforced composite plastics.

The housing 72 is provided with a removable lid or cover plate 74 having a depending rim 76 which fits around a portion of the side wall of the housing 72. In addition, the lid or cover plate 74 is provided with an enlarged central opening 78 in order to enable the display panel 64 to appear therethrough. A transparent cover plate 80, in the nature of a protective sheet, could also be

included in this opening 78 if desired. Furthermore, the removable lid or cover plate 74 is secured to the housing 72 in some manner as to preclude unauthorized opening as, for example, tamper-proof fasteners.

5 In order to preclude glare on the display panel 64, a top plate 69 is mounted on the upper end of the housing and carries at its outer end an angularly located somewhat downwardly struck visor 71. This construction is effective in reducing glare on the display screen 64, particularly from overhead light sources. The
10 top plate 69, which also functions as a visor, is optional in construction and can be eliminated in those environments where not required. It is also possible to provide a non-glare coating on the transparent cover plate 80, although the coatings themselves have not necessarily been fully effective in eliminating all glare.
15 In a preferred embodiment, the top plate 69 has an overall dimension from the rear of the housing of about 7". The lip 71 extends downwardly from the top plate 69 at a about a 45° angle. However, other sizes and angular relationships could be used, as may be required.

20 The transparent protective sheet 80 may be formed of a transparent plastic material, or otherwise it may be formed of glass. However, glass is not preferred due to the fact that it will crack or shatter with any rough handling. The transparent protective sheet 80 is retained in a U-shaped groove 82 formed at
25 the edge of the opening 78. This opening is formed by an integrally created U-shaped channel 84 surrounding the edge of the

opening 78, as best illustrated in Figure 7 of the drawings. In addition, the lid or cover member 74 is also provided with a U-shaped channel 86 perpendicularly arranged to the groove 82 and which is sized to receive the forwardly presented edge of the housing 72, as also best shown in Figure 7 of the drawings.

Figure 8 illustrates a slightly modified embodiment of the construction shown in Figure 7. In place of the formation of a U-shaped channel 84, a plurality of brackets or tabs 88 affixed to the inside of the cover member 74 surrounding the opening 78, are used to hold the transparent sheet 80 in a fixed position. The remaining portions of the lid are substantially identical to those shown and described in connection with Figure 7.

The operating components forming part of the display sign 20 are actually mounted on a chassis 90 disposed within the housing 72. The chassis 90 comprises a pair of longitudinally extending side plates 91 and which are connected by a bottom plate or chassis plate 93, as best shown in Figure 9 of the drawings. Moreover, and by reference to both Figures 9 and 10, it can be seen that the chassis 90 is disposed within the housing 72, as hereinafter described. Mounted on the upper surface of the chassis plate 92 are a pair of longitudinally extending frame bars 93 and which are connected by transversely extending cross-bars 94. Moreover, the longitudinally extending frame members 93 and the cross-bars 94 can be mounted on a supporting plate 96. Although the supporting plate 96 is provided in a preferred embodiment, it is not absolutely necessary and this plate could be eliminated, if desired.

The housing 72 is preferably comprised of an enclosing side wall 98 and a rear wall 100 which extends thereacross and thereby forms an interior chamber 102. The chassis 90 can be secured to this rear wall 100 by means of screws or other fasteners (not shown) which extend through the back plate. However, other forms of securement could be provided for this purpose, as hereinafter described.

The major operating components of the display sign are mounted on this chassis which is located within the housing 72, as aforesaid. These major operating components include a power supply 104 for the computer 26 and which also contain the display storage 60. A separate power supply 108 is also mounted on the chassis plate 96 and provides operating current for the other components of the display housing. The computer is effectively a microprocessor and contains the storage, as aforesaid, as well as a random access memory and a processor for controlling the display of a sign and also is operated from a control source at a remote location. Thus, and in this respect, the computer 106 is effectively a "slave" computer in that it receives instructions from the remote source and performs those instructions in the display sign by generating the proper display in accordance with the signals submitted to the computer 106.

Located on and secured to the upper surface of the chassis 90 is the display panel 64. In a preferred embodiment of the invention, the display panel is a plasma display. These display units are relatively thin and have a thickness in the order of

about 35mm. One of the preferred forms of display panel is made by Fujitsu and is identified as a "Full Color Plasma Display". These displays effectively operate as high-definition direct-view television monitors.

5 These displays generally contain about 640 horizontal display pixels and about 480 vertical pixels along with about 1920 horizontal display cells and 480 vertical display cells. Moreover, they operate with gradations of red, green and blue and present a viewing angle of about 140°. Internally, the display is usually
10 comprised of an IF controller, a data controller, a random access memory, and a driver controller. Nevertheless, since the plasma display is available in the art, it is therefore neither illustrated nor described in any further detail herein.

15 It is important to recognize that the display sign itself is generally fully self-contained and can literally be moved and operated at different locations. This is unlike the larger versions of display signs in which separate computer operated systems are required in order to operate the display panel itself. These display signs are effectively made with high definition and
20 high resolution display panels. The panels are flat, as aforesaid, and can be operated at standard line current, such as 120 volt AC current. As indicated previously, all of these plasma operated display panels are computer operated. In accordance with the present invention, the entire display panel, whether or not a
25 plasma panel, is computer operated from a computer source located within the display sign housing. In this sense, a remote source is

used to generate the display which is to be shown on the display panel. However, a plurality of displays can be pre-prepared and stored in the memory of the computer contained in the display panel housing. Nevertheless, the remote source would be used to revise or alter those displays, as may be required.

Based on the foregoing, the display panel of the invention can be described as a self-contained computer controlled flat panel display screen providing high resolution and definition. Although it is preferable to use the plasma operated display panel, it is possible to use those relatively flat computer controlled display panels which are not plasma operated but nevertheless still provide high resolution and definition and which are still nevertheless portable. Therefore, the display panel which is referred to as a computer controlled display panel is preferably one which is self-contained and includes a computer controlling a flat panel display screen of the type which provides both high resolution and definition and which is also relatively portable without the need for heavy transport equipment. This computer controlled display panel, when used in a display sign, also has a computer operating the display panel located in the display sign housing.

The aforesaid plasma display screens are relatively thin in their overall construction, having a thickness within the range of about 35mm, as aforesaid. Nevertheless, the flat panel display panel of the present invention is one which is deemed to have a thickness which does not exceed about six inches. Moreover, the entire display sign preferably does not have a thickness exceeding

about twelve inches. Although it is possible to use a computer for controlling the display panel outside of the sign housing, it is preferable to incorporate the computer in the sign housing.

The display panel used in the display system of the present invention differs substantially from that of a standard television type display. In a television display, the image will change at the display rate as, for example, fifty frames per second. Even though the image may not change such that the viewer perceives of a same display, the master pattern is such that the image on that screen nevertheless changes at the display rate. In the case of the present invention, the display on the screen may remain for essentially any period of time, including several seconds or several minutes, and there is no composite of frames to generate an image.

As indicated previously, the display system of the invention is portable. In other words, the entire display housing and stand can be moved from one location to another without heavy lifting and transporting equipment. The entire display panel and housing, along with the stand, could weigh as much as one hundred seventy pounds, but it is nevertheless liftable and movable by two or three persons. In contrast, with some of the large display signs which are presently used as, for example, a marquee over large hotels and the like, those displays may weigh several thousand pounds and require a hoist and like equipment to move same. Nevertheless, since the entire display housing can be transported from one location to another and, indeed, the display panel can be easily

transported from one location to another without the need for heavy cranes and the like, these display panels and, for that matter, the entire display sign is deemed to be portable.

5 The location of each of the aforesaid operating components within the housing does generate heat within the housing. For this purpose, the housing 72 is provided with a plurality of apertures 110 on the side walls thereof, as shown in Figure 9. In like manner, the chassis is provided with aligned apertures 112, as also shown in Figure 9. In this way, air-flow ventilation is allowed. 10 Moreover, and if desired, either exhaust fans or air in-take fans could be provided in adjacent relationship to the openings 110 and 112. Other types of ventilation means could also be provided, if desired.

15 It has been found in connection with the present invention that optimum flow and ventilation is achieved when a pair of oppositely disposed air intakes and a pair of oppositely disposed air outlets are provided. In addition, two fans are preferably used for air circulation throughout the housing. Thus, in the embodiment as shown in Figure 9, for example, there are a pair of 20 air inlets 110 and a pair of air outlets 112. Mounted on the bottom wall of the housing, as hereinafter described, are a pair of fans 124. This type of arrangement is highly effective in precluding condensation formation in the space between the actual display panel 64 and the transparent cover plate 80.

25 The entire housing 72 is mounted on a mounting plate or support plate 114, as best shown in Figure 10 of the drawings. In

this case, the support plate 114 is, in turn, secured to a wall or other support structure as, for example, the stand 66, as shown in Figure 12. The mounting plate 114 is provided with an upstanding protrusion 116 which extends through an opening (not shown) in the rear wall 100 of the housing. Thereafter, a locking pin 118 is provided for extension through the side walls of the housing and the opening in the protrusion 116. In this way, it is virtually impossible to remove the display sign from the mounting plate 114, unless one has authorized access to the interior of the housing 72. However, it should be understood that other means for mounting the housing 72 to the mounting plate 114 could be provided for this purpose.

The display panel 64 may be disposed on the upper surface of the chassis, as aforesaid, or otherwise located within the housing. In addition, it may be connected to the electronics and located within the cover plate 74 in adjacent relationship to the transparent cover plate 80. However, the display panel is preferably provided with an interference film or layer 130 which reduces heat introduction into the housing and operates as a type of interference film. Nevertheless, the interference film 130 could be located on the transparent cover plate 80 for this particular purpose. Figure 14 shows a stacked arrangement in which the display panel 64 is provided with the interference film 130 and the outer transparent cover plate 80. If desired, these components could be laminated together.

It is also possible to provide a spacer frame 132 between the transparent cover plate 80 and the display panel 64, thereby providing an intermediate isolated space 134, all as best shown in Figure 14. If the space 134 is properly insulated, then there is
5 little or no possibility of condensation forming in the interior thereof. Moreover, the space 134 could be evacuated during the construction of the assembly.

It has also been found that the plasma operated screens will generate radio frequency interference. Moreover, it has been found
10 that the interference film which is employed can be placed directly on the plasma operated display panel in order to preclude this interference. For this purpose, the interference layer is approximately 1.5 mil thick. It has been found that a plastic cover cannot be used for this purpose because of potential out
15 gassing.

The display system of the present invention provides a unique advantage which has not been heretofore available. The display can be generated in this case as an analog display. Prior art systems, on a limited basis, have used computers to generate a display on a
20 sign. However, that display is necessarily generated in a digital format and, thus, has significant limitations on the quality and the ability of a particular display to be generated. Contrariwise, in the present invention, a display, which may be generated from a photographic image, can be essentially recreated on a display sign
25 from a remote source.

The display system of the present invention not only operates as a true display sign per se, but it is also effective in operating as a type of product or service promotion enhancing medium. Thus, not only does the display sign present a display as such, but the manner in which the display system is operated literally has been found to provide a type of advertising or promotional medium. For this purpose, the display stand itself may be provided with an arrangement for displaying products. Referring again to Figure 12, it can be seen that a plurality of upstanding dividers 140 (four as shown) divide the upper surface of the base 68 into individual compartments 142. Various products can be displayed directly in these individual compartments. As a simple example, if the display stand were used in a supermarket, cans of a specified vegetable may be literally stacked in one of the compartments 142, packaged meat products could literally be displayed in another one of the compartments, etc. For this purpose, the construction of the base can vary and, for that matter, additional shelves can be mounted on the legs 70 in order to increase the display space.

In another embodiment of the invention, the display sign can be used as a type of point of sale promotion enhancer. Referring Figure 13, for example, it can be observed that there is a display sign 20 also mounted on a stand 68 having an upstanding leg 70. For purposes of providing information, such as coupons which could be used, e.g. in a drugstore, a rack 144 is mounted on the leg 70, as shown in Figure 13. This rack can be sub-divided into

individual compartments for holding various types of informational sheets which may be picked up by a user. In addition, and for purposes of making reservations when a display advertises a particular feature or event, or when the display advertises a hotel, for example, a telephone 146 can also be connected to the outer housing 72. This telephone 146 could either be a dialing telephone or one which is connected directly to a source capable of taking a reservation or otherwise booking an arrangement for the caller. Thus, as a simple example, the display sign could be generating displays featuring a particular hotel and if the observer is pleased with the displays generated, he or she can merely pick up the telephone handset, as shown in Figure 13, and immediately access an operator or other agent capable of making the reservation or booking the particular event or hotel room for the caller.

These few features alone illustrate the wide versatility capable of being achieved with the display system of the present invention. In this respect, the display system can generate a type of "streaming media", that is, it possesses the capability of presenting continuously groups of advertisements which may be run together end on end and, for that matter, can even blend advertisements. This may be particularly advantageous when a product display is also set up on the base, as previously described. In addition, the display can actually be animated with a type of 3-D presentation. Various graphic aids can also be used. As a simple example, the display can be generated initially from

top to bottom or from bottom to top. Figure 12 shows, for example, a display which is coming from the lower right hand corner of the display screen and which is being increased in size over time. Thereafter, the next display could come from a different corner or from a side, top or bottom of the screen. This type of presentation has been found to generate a great deal of attention.

In addition to the foregoing, the product or service which is being generated can also be animated in order to obtain attention of individuals. Furthermore, sound can be generated. Thus, as a simple example, on each occasion when a new product or service is offered or, for that matter, when images of a particular product or service being offered changes, a bell can ring or other noise can be generated in order to catch the viewer's attention. As indicated previously, the basket or rack enables hand-outs to the viewer and, thus, represents a type of "uplift" advertising, that is, it causes people to purchase more of a particular product or service than they would otherwise purchase.

The display system of the invention also has the capability, particularly when operated from a remote source, of causing alterations of the display at any point in time. Thus, for example, if an eight ounce box of a particular product is being displayed, it is possible to immediately cause a four ounce box of that same product or, for that matter, another product to be presented over the image of the eight ounce box of product. Moreover, with the animation and the fact that the display can be

generated in essentially any fashion, it is possible to place a product or service in a most favorable light.

It is also possible to operate a plurality of these display signs at a single location or at different locations from one remote source. Moreover, all of the display signs could be operated simultaneously or individually. In addition, all of the display signs could be connected together through a single telephone circuit enabling the access of all of the individual display panels.

One of the features of the display stand of the invention is the fact that it actually attracts the viewer, that is, viewers will literally stand in front of the display in order to view same. This has been found to be important in that it actually increases the purchase or other acquisition of the service or product. Thus, the display stand not only functions to merely advise of the availability of a product or service, but it provides information about that product or service and, in addition, promotes and enhances the product and service so that the interest of the viewer is increased in that product and service by viewing the display. In this way, the display device not only functions to present displays, but it actually functions to enhance and increase the advertising appeal of a particular product or service.

Thus, there has been illustrated and described a unique and novel display system which enables a display sign to be operated from a remote source and where a display can be generated at the sign based on signals from the remote source and which are

transmitted to the display sign for generation of an analog display thereon. The display system and the display sign forming a part thereof thereby fulfill and meet all of the objects and advantages which have been sought. It should be understood that many changes, modifications, variations and other uses and applications will become apparent to those skilled in the art after considering this specification and the accompanying drawings. Therefore, any and all such changes, modifications, variations and other uses and applications which do not depart from the spirit and scope of the invention are deemed to be covered by the invention.